

Car2U Programming Instructions

Rolling Code Transmitter Instructions:

Step 1: Firmly press the 2 outer Car2U[®] System buttons for 1 to 2 seconds then release.

Step 2: Go to the garage to locate the garage door opener motor and press its "learn" button. You will have 10 to 30 seconds to return to your vehicle and complete the following steps.

Step 3: Press and hold the Car2U[®] System button you would like to use to control the garage door. Immediately release the button once the garage door moves. When the button is released, the indicator light will begin to blink rapidly until programming is complete.

Step 4: Press and release the button again. The garage door should move, confirming that programming was successful. If your garage door opener does not operate following these steps, repeat the previous steps or download the complete "Programming Instructions."

Fixed Code Transmitter Instructions:

Step 1: Open the battery cover and record the DIP switch settings from left to right for all 8 to 12 switches. (Use the figure below.)

Switch position	1	2	3	4	5	6	7	8	9	10	11	12
Up, + or on	left											
middle, 0 or neutral	middle											
Down, - or off	right											

Step 2: To input these positions, simultaneously press all 3 Car2U[®] System buttons for a few seconds and then release to put the device into programming mode. The indicator lights will blink slowly. Enter your corresponding DIP switch settings from left to right, in order, into your Car2U[®] System by pressing and releasing the buttons corresponding to the settings you circled.

Step 3: After inputting switch settings, simultaneously press all 3 Car2U[®] System buttons and release. The indicator lights will turn on. Press and hold the Car2U[®] System button you would like to use to control the garage door. Release the button once the garage door moves.

Step 4: The indicator light will blink rapidly until programming is complete. If your garage door opener does not operate following these steps, repeat the previous steps or download the complete "Programming Instructions."

Important: When programming your Car2U[®] System, be sure that people and objects are out of the way to prevent potential harm or damage.

Important: Do not use the Car2U[®] System with any garage door opener that lacks safety stops and reverse features as required by U.S. Federal Safety Standards. This includes any garage door opener manufactured before April 1, 1982.